SEGWAY

SEGWAY AT10

97 HP DYNAMIC POWER

125km/h Max Speed
8.0s 0-100km/h Acceleration
38° Climbing Angle

SMART MOVING APP

Remote access to the real-time data of vehicle through smart moving APP.
Airlock / EPS Settings / Wireless Team Up/ Security Guarantee / Real-Time Data

LOW HEAT IMPACT

Outstanding heat dissipation provides excellent rider comfort, perfect for long riding days.

MUD VERISION

Customized for muddy terrain, offer best performance even in extreme conditions.

SUPERIOR CAPACITY

Rack Load Capacity: 100kg
Towing Capacity: 700kg

30" TIRES

30" tires greatly increase the ground clearance to 320 mm. (Wide Version)

Segway reserves the right to change specifications, models or pricing at any time without incurring obligations.

SPECIFICATIONS	AT10 EPS	AT10 PREMIUM	AT10 W PREMIUM	AT10 W MUD
ENGINE	999cc 4-Stroke Parallel-Twin Cylinder DOHC	999cc 4-Stroke Parallel-Twin Cylinder DOHC	999cc 4-Stroke Parallel-Twin Cylinder DOHC	999cc 4-Stroke Parallel-Twin Cylinder DOHC
HORSEPOWER	97 HP	97 HP	97 HP	97 HP
TRANSMISSION	Automatic CVT	Automatic CVT	Automatic CVT	Automatic CVT
DIFFERENTIAL LOCK	Front	Front & Rear	Front /Rear	Front /Rear
EPS	√	√	√	√
DIMENSIONS	94.9 x 49.6 x 57.2" (241.0 x 125.9 x 145.2 cm)	94.9 x 49.6 x 57.2" (241.0 x 125.9 x 145.2 cm)	95.6 x 58.6 x 60.2" (242.9 x 148.9 x 153.0 cm)	95.6 x 58.6 x 60.2" (242.9 x 148.9 x 153.0 cm)
WHEELBASE	57.3"(145.5 cm)	57.3"(145.5 cm)	57.3"(145.5 cm)	57.3"(145.5 cm)
GROUND CLEARANCE	10.8"(27.5 cm)	10.8"(27.5 cm)	12.6"(32 cm)	12.6"(32 cm)
FUEL CAPACITY	6.1 Gal (23 L)	6.1 Gal (23 L)	6.1 Gal (23 L)	6.1 Gal (23 L)
TOWING CAPACITY	1,543 LB (700 kg)	1,543 LB (700 kg)	1,543 LB (700 kg)	1,543 LB (700 kg)
PAYLOAD CAPACITY	594 LB (270 kg)	594 LB (270 kg)	594 LB (270 kg)	594 LB (270 kg)
FRONT SUSPENSION	Dual A-Arm; Front Travel:7.3"	Dual A-Arm; Front Travel:7.3"	Dual A-Arm; Front Travel:6.8"	Dual A-Arm; Front Travel:6.8"
REAR SUSPENSION	Dual A-Arm; Rear Travel: 8.3"	Dual A-Arm; Rear Travel: 8.3"	Dual A-Arm; Rear Travel: 8.3"	Dual A-Arm; Rear Travel: 8.3"
SHOCKS	Oil Shock	Gas Shock	Gas Shock	Gas Shock
WHEELS	14" Steel Rim	14" Alum Rim with Beadlock	14" Alum Rim with Beadlock	14" Alum Rim with Beadlock
TIRES	Front 27×09 R14 Rear 27×11 R14	Front 27×09 R14 Rear 27×11 R14	Front 30×09 R14 Rear 30×09 R14	Front 30×09 R14 Rear 30×09 R14
BRAKES	3-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc
RACK	Front & Rear Steel Rack	Front & Rear Plastic Rack	Front & Rear Plastic Rack	Front & Rear Plastic Rack
LAMP	Halogen	LED	LED	LED
BACKREST	√	√	√	√
SMART MOVING APP	Included	Included	Included	Included
WINCH	4,500 LB	4,500 LB	4,500 LB	4,500 LB
PERSON CAPACITY	2	2	2	2
HANDLEBAR GUARD	√	√	√	√
COLORS	Tensive Red & Grey / Matt Black / Desert Yellow / TRUETIMBER® Prairie Camo			